






1	LEDK
2	LEDK
3	GND
4	VCC
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	CLK
31	DISP
32	HSYNC
33	VSYSN
34	DEN
35	NC
36	GND
37	XR
38	YD
39	XL
40	YU



- 技术要求:
- 带*尺寸为重点尺寸,带()尺寸为参考尺寸
 - LCD切割断面崩边≤1/3(单层LCD厚度)
 - 平面翘曲度≤0.35mm
 - 符合RoHS指令
 - 工作温度: -20℃~70℃
 - 储存温度: -30℃~80℃
 - 建议TV A开窗比LCD A.A单边大0.4mm
 - 泡棉开窗比LCD A.A单边大0.3mm

REV	STCN	DESCRIPTION	PIC	DATE
C		更换背光,修改背光PCB盘	XW	
B		更改IC,修改PCB外形	XW	
A		首次发行	XW	

PART DESCRIPTION		LCM		深圳驰宇微科技有限公司	
DESIGNED		CHECKED		MODEL NAME	CYWTF1043B005
APPROVED				PART NUMBER	
				DRAWING REV.	A
				PART NUMBER VER.	N/A